

SAFETY DATA SHEET

According to the Brazilian Standard ABNT NBR 14725-4:2014 According to the Brazilian Standard ABNT NBR 14725-4:2014, Safety Data Sheets (SDS) must be supplied for dangerous substances or preparations. This product does not meet the classification criteria of the standard. Therefore, the content requirements in each section do not apply.

CARBON BLACK

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 <u>Product Identifier</u>

Chemical name:

Carbon Black

This SDS is valid for the following grade

	ASTM			Birla Carbon™				Other
N110	N339	N683	1001	1062	2013	2127	2439	PM0620
N115	N343	N762	1003	1065	2033	2207	2447	PM0630
N121	N347	N765	1004	1076	2041	2330	2451	PM0710
N134	N351	N772	1007	1077	2045	2340	2475	JC300
N220	N375	N774	1029	1083	2056	2341		JETCARB300P
N231	N539		1031	1095	2109	2342		
N234	N550		1034	1155	2115	2343		
N299	N630		1041	1455	2117	2422		
N326	N650		1051	1466	2123	2432		
N330	N660		1056	2005	2124	2433		

1.2 <u>Recommended use of the chemical and restrictions on use</u> Recommended use: Additive for plastic and rubber; pigment; chemical reagent, additive for batteries, refractories, various.

Restrictions on use: Pigments in tattoo colors for humans.

1.3 Details of the supplier of the safety data sheet
See Section 16
Birla Carbon U.S.A., Inc.
1800 West Oak Commons Court
Marietta, Georgia 30062, USA
+1 (800) 235-4003 or +1 (770) 792-9400

Email Address: <u>BC.HSE@adityabirla.com</u>

Emergency Telephone Numbers:

Brazil VERISK3E: +55 11 4349 1907

US & Canada VERISK3E: +1 866 519 4752

2.1	Classification of	<u>Classification of the substance or mixture</u>					
	Brazil:	Not a hazardous substance or mixture according to Brazilian Standard ABNT NBR 14725-2.					
2.2	<u>Label elements</u>						
	Pictogram:	None					

Signal Word: None Hazard Statement: None

Precautionary Statement: None

2.3 <u>Other hazards</u>

This substance is classified as hazardous as a combustible dust by the United States 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Hazardous Products Regulation (HPR) 2015. The signal word, hazard statement and precautionary statements in the United States and Canada are: WARNING May form combustible dust concentrations in air. Keep away from all ignition sources including heat, sparks and flame. Prevent dust accumulations to minimize explosion hazard. Do not expose to temperatures above 300°C. Hazardous products of combustion can include carbon monoxide, carbon dioxide, oxides of sulfur, and organic products.

Eye:	May cause reversible mechanical irritation.
Skin:	May cause mechanical irritation, soiling, and drying of skin. No cases of sensitization in humans have been reported.
Inhalation:	Dust may be irritating to the respiratory tract. Provide local exhaust ventilation. See Section 8.
Ingestion:	Adverse health effects are not expected.
Carcinogenicity:	Carbon black is listed by the International Agency for Research on Cancer (IARC) as a Group 2B substance (<i>possibly carcinogenic to humans</i>). See Section 11.

 3.1
 Substance

 3.1.1
 Carbon Black (amorphous) 100%

 3.1.2
 CAS Number:
 1333-86-4

 3.1.3
 Synonyms:
 carbon black, furnace black

 SECTION 4: First-aid measures

 4.1
 Description of first-aid measures

Inhalation: Take affected persons into fresh air. If necessary, restore normal breathing through standard first aid measures.

- Skin: Wash skin with mild soap and water. If symptoms persist, seek medical attention.
- Eye: Rinse eyes thoroughly with large volumes of water keeping eyelids open. If symptoms develop, seek medical attention.
- Ingestion: Do not induce vomiting. If conscious, give several glasses of water. Never give anything by mouth to an unconscious person.
- 4.2 <u>Most important symptoms, both acute and delayed</u> Symptoms: Irritating to the eyes and respiratory tract if exposed above the occupational exposure limits. See Section 2.
- 4.3 <u>Indication of any immediate medical attention and special treatment needed</u> Note to physicians: Treat symptomatically

SECTIO	DN 5: Fire-fighting measures					
5.1	Extinguishing media					
	Suitable extinguishing media:	Use foam, carbon dioxide (CO_2), dry chemical, or water fog. A fog spray is recommended if water is used.				
	Unsuitable extinguishing media:		use high pressure media which could cause the formation of a ally explosible dust-air mixture.			
5.2	Special hazards arising from the su	bstance o	or mixture			
	Special hazards arising from the ch	emical:	It may not be obvious that carbon black is burning unless the material is stirred and sparks are apparent. Carbon black that has been on fire should be closely observed for at least 48 hours to ensure no smoldering material is present.			
	Hazardous Combustion Products:		Carbon monoxide (CO), carbon dioxide (CO ₂), and oxides of sulfur.			
5.3	<u>Advice for fire fighters</u> Special protective equipment for fi	re-fighter	rs: Wear full protective firefighting gear, including self- contained breathing apparatus (SCBA). Wet carbon black produces very slipper walking surfaces.			

SECTION 6: Accidental release measure	res					
6.1 <u>Personal precautions, protective equipment and emergency procedures</u>						
Personal precautions:	Wet carbon black produces slippery walking surfaces. Avoid dust formation.					
	Wear appropriate personal protective equipment and respiratory protection. See Section 8.					
For emergency responders:	Use personal protective equipment recommended in section 8.					
6.2 Environmental precautions						
Environmental precautions:	Carbon black poses no significant environmental hazards. Contain spilled product on land, if possible. As a matter of good practice, minimize contamination of sewage water, soil, groundwater, drainage systems, or bodies of water.					
6.3 Methods and materials for co	ntainment and cleaning up					
Methods for containment:	Prevent further leakage or spillage if safe to do so.					
Methods for cleaning up:	Small spills should be vacuumed when possible. Dry sweeping is not recommended. A vacuum equipped with high efficiency particulate air (HEPA) filtration is recommended. If necessary, light water spray will reduce dust for dry sweeping. Large spills may be shoveled into containers. See Section 13.					
SECTION 7: Handling and storage	SECTION 7: Handling and storage					

7.1 <u>Precautions for safe handling</u>

Advice on safe handling: Avoid dust formation. Do not breathe dust. Provide appropriate local exhaust to minimize dust formation. Do not use compressed air.

Take precautionary measures against static discharges. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Grounding of equipment and conveying systems may be required under certain conditions. Safe work practices include the elimination of potential ignition sources in proximity to

carbon black dust; good housekeeping to avoid accumulations of dust on all surfaces; appropriate exhaust ventilation design and maintenance to control airborne dust levels to below the applicable occupational exposure limit. If hot work is required, the immediate work area must be cleared of carbon black dust.

General hygiene considerations: Handle in accordance with good industrial hygiene and safety practices.

7.2 <u>Conditions for safe storage, including any incompatibilities</u>

Storage conditions: Keep in a dry, cool, and well-ventilated location. Store away from heat, ignition sources, and strong oxidizers.

Carbon black is not classifiable as a Division 4.2 self-heating substance under the UN test criteria. However, current UN criteria for determining if a substance is self-heating is volume dependent. This classification may not be appropriate for large volume storage container.

Before entering vessels and confined spaces containing carbon black, test for adequate oxygen, flammable gases and potential toxic air contaminants. Do not allow dust to accumulate on surfaces.

Incompatible materials: Strong oxidizers.

	ON 8: Exposure conti	· · · ·			
.1	Control parameter				
	Exposure guideline	es: Representative occupational exposure limits currently available for carbon black (CAS number: 1333-86-4).			
	<u>Country</u>	Concentration, mg/m3			
	Argentina	a 3.5, TWA			
	Brazil	3.5, TWA			
	Colombia	a 3.0, TWA, inhalable			
	Mexico	3.5, TWA			
	United St	tates 3.5, TWA, OSHA-PEL			
		3.0, TWA, ACGIH-TLV®, inhalable			
		3.5, TWA, NIOSH-REL			
	*Please consult the current version of the standard or regulation that may apply to your operations. ACGIH [®] American Conference of Governmental Industrial Hygienists				
		milligrams per cubic meter			
	-	Derived no-effect level			
	NIOSH	National Institute for Occupational Safety and Health			
		Occupational Safety and Health Administration			
		permissible exposure limit			
	REL	recommended exposure limit short-term exposure limit			

TWA time weighted average, eight (8) hours unless otherwise specified

Predicted No Effect Concentration: Not applicable

8.2 <u>Exposure controls</u>

Engineering controls: Use process enclosures and/or exhaust ventilation to keep airborne dust concentrations below the occupational exposure limit.

Personal Protective Equipment (PPE)

Respiratory: Approved air purifying respirator (APR) should be used where airborne dust concentrations are expected to exceed occupational exposure limits. Use a positive-pressure, air supplied respirator if there is any potential for uncontrolled release, exposure levels are not known, or in circumstances where APRs may not provide adequate protection.

When respiratory protection is required to minimize exposures to carbon black, programs should follow the requirements of the appropriate governing body for the country, province or state. Selected references to respiratory protection standards are provided below:

- OSHA 29CFR1910.134, Respiratory Protection
- CR592 Guidelines for Selection and Use of Respiratory Protective Devices (CEN)
- German/European Standard DIN/EN 143, Respiratory Protective Devices for Dusty Materials (CEN)

Hand protection:	Wear protective gloves. Use a barrier cream. Wash hands and skin with mild soap and water.
Eye/face protection:	Wear safety glasses or goggles.
Skin protection:	Wear general protective clothing to minimize skin contact. Wash clothing daily. Work clothes should not be taken home.
Other:	Emergency eyewash and safety showers should be in close proximity. Wash hands and face thoroughly with mild soap before eating or drinking.

Environmental exposure controls: in accordance with all local legislation and permit requirements.

SECTION 9: Physical and chemical properties					
9.1	Information on basic physical and chemical properties				
	Appearance:	powder or pellet			
	Color:	black			
	Odor:	odorless			
	Odor threshold:	not applicable			
	Melting point/freezing point:	not applicable			
	Boiling point/range:	not applicable			
	Vapor pressure:	not applicable			
	Vapor Density:	not applicable			
	Oxidizing properties:	not applicable			
	Flash Point:	not applicable			
	Flammability:	not flammable			
	Explosive properties:	Dust may form explosible mixture i	n air		
	Explosion limits (air):				
	Upper:	not available			
	Lower:	50 g/m ³ (dust)			
	Evaporation rate:	not applicable			
	Density: (20ºC):	$1.7 - 1.9 \text{ g/cm}^3$			
	Bulk density:	1.25-40 lb/ft ³ , 20-640 kg/m ³			
	Pellets:	$200-680 \text{ kg/m}^3$			
CA	RBON BLACK	Page 5 of 12	Revised 25.08.2021 Supersedes 08.01.2021		

0.2	Powder (fluffy): Solubility (in Water): pH value: (ASTM 1512): Partition coefficient (n-octanol/wat Viscosity: Decomposition temperature: Auto-ignition temperature: Minimum Ignition temperature: Minimum ignition energy: Ignition energy: Maximum absolute explosion press Maximum rate of pressure rise: Burn Velocity: Kst Value: Dust explosion classification: Decomposition temperature:	not applicable not applicable >140°C >500°C (BAM Furnace)(VDI 2263) >315°C (Godberg-Greenwald Furnace)(VDI 2263) >10,000 mJ (VDI 2263) not available
9.2	<u>Other information</u> Not available	
SECTIO	N 10: Stability and reactivity	
10.1	Reactivity	
	Reactivity:	May react exothermically upon contact with strong oxidizers.
10.2	<u>Chemical stability</u> Stability:	Stable under normal ambient conditions.
	Explosion data Sensitivity to mechanical impact:	Not sensitive to mechanical impact
	Sensitivity to static discharge:	Dust may form explosible mixture in air. Avoid dust formation. Do not create a dust cloud. Take precautionary measures against static discharges. Ensure all equipment is earthed/grounded before beginning transfer operation.
10.3	<u>Possibility of hazardous reactions</u> Hazardous polymerization:	Does not occur.
	Possibility of hazardous reactions:	None under normal conditions.
10.4	<u>Conditions to avoid</u> Conditions to avoid:	Avoid high temperatures >400°C (>752°F) and sources of ignition.
10.5	Incompatible materials Incompatible materials:	Strong oxidizers.
10.6	Hazardous decomposition products Hazardous decomposition products	<u>s</u> s: Carbon monoxide, carbon dioxide, organic products of combustion, oxides of sulfur.

SECTIO	ON 11: Toxicological information	
11.1	Information on toxicological effects	
	Acute Toxicity:	

Oral LD50:	LD ₅₀ (rat) > 8000 mg/kg	(Equivalent to OECD TG 401)	
Inhalation LD50:	No data available		
Dermal LD50:	No data available		
Skin corrosion/irritation:	Edema = 0 (max. attaina	inable irritation score: 4)	
Serious eye damage/irritation:		ble irritation score: 4) rritation score: 2) ttainable irritation score: 3) nable irritation score: 4)	
Sensitization:		r Test): Not sensitizing (OECD TG 406)	
	<u>Assessment: Not sensitizing in animals.</u> No cases of sensitization in humans have been reported.		
Germ cell mutagenicity:	test) and other <i>in vitro</i> organic solvent extracts mutagenic effects. Orgar of polycyclic aromatic bioavailability of these	not suitable to be tested directly in bacterial (Ames systems because of its insolubility. However, when of carbon black have been tested, results showed no nic solvent extracts of carbon black can contain traces hydrocarbons (PAHs). A study to examine the PAHs showed that they are very tightly bound to bioavailable (Borm, 2005).	
	were reported in alvere exposure to carbon blace be rat-specific and a con inflammation and release	tal investigation, mutational changes in the <i>hprt</i> ene blar epithelial cells in the rat following inhalation ck (Driscoll, 1997). This observation is considered to asequence of "lung overload," which leads to chronic e of reactive oxygen species. This is considered to be effect and, thus, carbon black itself would not be enic.	
	a threshold effect and i chronic inflammation a mechanism is considered	tagenicity in rats occurs by mechanisms secondary to s a consequence of "lung overload," which leads to and the release of genotoxic oxygen species. This d to be a secondary genotoxic effect and, thus, carbon considered to be mutagenic.	
Carcinogenicity:	Animal toxicity	Rat, oral, duration 2 years. Effect: no tumors.	
		Mouse, oral, duration 2 years. Effect: no tumors.	
		Mouse, dermal, duration 18 months. Effect: no skin tumors.	
		Rat, inhalation, duration 2 years.	
RBON BLACK	Page 7 of 12	Revised 25.08.2021	

Target organ: lungs. Effect: inflammation, fibrosis, tumors.

Note: Tumors in the rat lung are considered to be related to "lung overload" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific (ILSI, 2000). Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions.

Mortality studies (human data)

A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plants studied; however, the increase was not related to the dose of carbon black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorahan, 2001 (UK study), found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (Dell, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was *inadequate* (IARC, 2010).

Since the IARC evaluation of carbon black, Sorahan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorahan and Harrington.

Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

IARC cancer classification

In 2006 IARC re-affirmed its 1995 finding that there is *"inadequate evidence"* from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is *"sufficient evidence"* in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is *"possibly carcinogenic to humans (Group 2B)"*. This conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was *"sufficient evidence"* that carbon black extracts can cause cancer in animals (Group 2B).

ACGIH cancer classification

Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

<u>Assessment:</u> Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rat tumors are a result of a secondary non-genotoxic mechanism associated with the phenomenon of lung overload. This is a species-specific mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for

Specific Target Organ Toxicity – Repeated Exposure (STOT-RE), cites lung overload under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk of carcinogenicity.

Reproductive and developmental toxicity: <u>Assessment:</u> No effects on reproductive organs or fetal development have been reported in long-term repeated dose toxicity studies in animals.

Specific target organ toxicity – single exposure (STOT-SE):

<u>Assessment</u>: Based on available data, specific target organ toxicity is not expected after single oral, single inhalation, or single dermal exposure.

Specific target organ toxicity – repeated exposure (STOT-RE):

Animal toxicity

Repeated dose toxicity: inhalation (rat), 90 days, No Observed Adverse Effect Concentration (NOAEC) = 1.1 mg/m³ (respirable)

Target organ/effects at higher doses are lung inflammation, hyperplasia, and fibrosis.

Repeated dose toxicity: oral (mouse), 2 yrs, No Observed Effect Level (NOEL) = 137 mg/kg (body wt.)

Repeated dose toxicity: oral (rat), 2 yrs, NOEL = 52 mg/kg (body wt.)

Although carbon black produces pulmonary irritation, cellular proliferation, fibrosis, and lung tumors in the rat under conditions of lung overload, there is evidence to demonstrate that this response is principally a species-specific response that is not relevant to humans.

Morbidity studies (human data)

Results of epidemiological studies of carbon black production workers suggest that cumulative exposure to carbon black may result in small, non-clinical decrements in lung function. A U.S. respiratory morbidity study suggested a 27 ml decline in FEV₁ from a 1 mg/m³ 8 hour TWA daily (inhalable fraction)

exposure over a 40-year period (Harber, 2003). An earlier European investigation suggested that exposure to 1 mg/m^3 (inhalable fraction) of carbon black over a 40-year working lifetime would result in a 48 ml decline in FEV₁ (Gardiner, 2001). However, the estimates from both studies were only of borderline statistical significance. Normal age-related decline over a similar period of time would be approximately 1200 ml.

In the U.S. study, 9% of the highest non-smokers exposure group (in contrast to 5% of the unexposed group) reported symptoms consistent with chronic bronchitis. In the European study, methodological limitations in the administration of the questionnaire limit the conclusions that can be drawn about reported symptoms. This study, however, indicated a link between carbon black and small opacities on chest films, with negligible effects on lung function.

Assessment:

Inhalation - Applying the guidelines of self-classification under GHS, carbon black is not classified under STOT-RE for effects on the lung. Classification is not warranted on the basis of the unique response of rats resulting from "lung overload" following exposure to poorly soluble particles such as carbon black. The pattern of pulmonary effects in the rat, such as inflammation and fibrotic responses, are not observed in other rodent species, non-human primates, or humans under similar exposure conditions. Lung overload does not appear to be relevant for human health. Overall, the epidemiological evidence from well-conducted investigations has shown no causative link between carbon black exposure and the risk of non-

malignant respiratory disease in humans. A STOT-RE classification for carbon black after repeated inhalation exposure is not warranted.

Oral: Based on available data, specific target organ toxicity is not expected after repeated oral exposure.

Dermal: Based on available data and the chemical-physical properties (insolubility, low absorption potential), specific target organ toxicity is not expected after repeated dermal exposure.

Aspiration hazard: <u>Assessment:</u> Based on industrial experience and the available data, no aspiration hazard is expected.

SECTIO	ON 12: Ecological information	
12.1	Toxicity	
	Aquatic toxicity:	
	Acute fish toxicity:	LCO (96 h) 1000mg/l, Species: <i>Brachydanio rerio</i> (zebrafish), Method: OECD Guideline 203
	Acute invertebrate toxicity:	EC50 (24 h) > 5600 mg/l, Species: <i>Daphnia magna</i> (waterflea), Method: OECD Guideline 202
	Acute algae toxicity:	EC50 (72 h) >10,000 mg/l, NOEC 10,000 mg/l, Species: <i>Scenedesmus subspicatus</i> , Method: OECD Guideline 201
	Activated sludge:	EC0 (3 h) > 400 mg/l, EC10 (3h): ca. 800 mg/l, Method: DEV L3 (TTC test)
12.2	Persistence and degradability	

Not soluble in water. Expected to remain on soil surface. Not expected to degrade.

- 12.3 <u>Bioaccumulative potential</u> Not expected because of the physicochemical properties of the substance.
- 12.4 <u>Mobility in soil</u> Not expected to migrate. Insoluble.
- 12.5 <u>Results of PBT and vPvB assessment</u> Carbon black is not a PBT or a vPvB.
- 12.6 <u>Other adverse effects</u> Not available.

SECTIC	SECTION 13: Disposal considerations			
13.1	Waste treatment methods			
	Product disposal: Product should be disposed of in accordance with the regulations issued appropriate federal, provincial, state, and local authorities.			
	Container/Packaging disp	bosal: Empty packaging must be disposed of in accordance with national and local laws.		

SECTION 14: Transport information

The International Carbon Black Association organized the testing of seven ASTM reference carbon blacks according to the UN method, Self-Heating Solids. All seven reference carbon blacks were found to be "Not a self-heating substance of Division 4.2." The same carbon blacks were tested according to the UN method, Readily Combustible Solids and found to be "Not a readily combustible solid of Division 4.1;" under current UN Recommendations on the Transport of Dangerous Goods.

The following organizations do not classify carbon black as a "hazardous cargo" if it is "carbon, non-activated, mineral origin." Birla Carbon's carbon black products meet this definition.

DOT	IMDG RID ADR	ICAO (air)	<u>IATA</u>	<u>ANTT</u>
14.1 14.2 14.3 14.4	UN/ID No Proper shipping name Hazard class Packing group	Not regulated Not regulated Not regulated Not regulated		

SECTION 15: Regulatory information

15.1 International Inventories:

Carbon black, CAS number 1333-86-4, appears on the following inventories:

Australia:	AICS
Canada:	DSL
China:	IECSC
Europe (EU):	EINECS (EINECS-RN: 215-609-9)
Japan:	ENCS
Korea:	KECI
Philippines:	PICCS
Taiwan:	TCSI
New Zealand:	NZIOC
USA:	TSCA

SECTION 16: Other Information			
Contact Information			
Birla Carbon U.S.A., Inc.	Birla Carbon Brasil Ltda.	Birla Carbon Egypt S.A.E.	Birla Carbon China (Weifang)
370 Columbian Chemicals Lane	Estrada Renê Fonseca S/N	El-Nahda Road	Co., Ltd.
Franklin, LA 70538-1149, U.S.A.	Cubatão SP Brazil	Amreya, Alexandria, Egypt	Binhai Economic Development
Telephone +1 337 836 5641	CEP 11573-904	+20 3 47 70 102	Zone
	PABX Operator +55 13 3362 7100		Weifang, Shandong, 262737,
			PRC
			Telephone +86 (0536) 530 5978
Birla Carbon U.S.A., Inc.	Birla Carbon Italy S.R.L.	Birla Carbon India Private Limited	Birla Carbon China (Jining) Co.
3500 South Road S	Via S Cassiano, 140	K-16, Phase II, SIPCOT Industrial	Ltd.
Ulysses, KS 67880-8103, U.S.A.	I - 28069 San Martino di Trecate	Complex	No. 6, Chenguang Road, Jibei
Telephone +1 620 356 3151	(NO) Italy	Gummidipoondi – 601201	High-Tech Industry Park Zone
	Telephone +39 0321 7981	Dist: Thiruvallur, Tamil Nadu	Jining City, Shandong Province
		India	The People's Republic of China,
		+91 44 279 893 01	272000
			Telephone +86 (0537) 677 9018
Birla Carbon Canada Ltd.	Birla Carbon Hungary Ltd.	Birla Carbon India Private Limited	Birla Carbon Korea Co., Ltd.
755 Parkdale Ave. North	H - 3581 Tiszaújváros	Village Lohop, Patalganga,	#1-3, Ulha-Dong
P.O. Box 3398, Station C	P.O.B. 61, Hungary	Taluka: Khalapur	Yeosu city, cheonnam 555-290,
Hamilton, Ontario L8H 7M2	Telephone +36 49 544 000	Dist.: Raigad 410207	Korea
Canada		Maharashtra, India	Telephone 82-61-688-3330
Telephone +1 905 544 3343		+91 22 2192 250133	

Birla Carbon Brasil Ltda.	Birla Carbon Spain, S.L.U.	Birla Carbon India Private Limited	Birla Carbon Thailand Public Co.
Via Frontal km, 1, S/N. Polo	Carretera Gajano-Pontejos	Murdhwa Industrial Area	Ltd.
Petroquimico	39792 Gajano, Cantabria	P.O. Renukook, Dist: Sonebhadra	44 M.1, T. Posa, A. Muang
Camaçari Bahia Brazil	Apartado 283, Santander, Spain	U.P. Pin – 231 217	Angthong 14000
CEP 42.810-320	Telephone +34 942 503030	India	+66 35 672 150-4
Telephone +55 71 3616 1100		+91 5446 252 387/88/89/90/91	

References:

Borm, P.J.A., Cakmak, G., Jermann, E., Weishaupt C., Kempers, P., van Schooten, FJ., Oberdorster, G., Schins, RP. (2005) Formation of PAH-DNA adducts after in-vivo and vitro exposure of rats and lung cell to different commercial carbon blacks. Tox. Appl. Pharm. 1:205(2):157-67.

Buechte, S, Morfeld, P, Wellmann, J, Bolm-Audorff, U, McCunney, R, Piekarski, C. (2006) Lung cancer mortality and carbon black exposure – A nested case-control study at a German carbon black production plant. J.Occup. Env.Med. 12: 1242-1252.

Dell, L, Mundt, K, Luipold, R, Nunes, A, Cohen, L, Heidenreich, M, Bachand, A. (2006) A cohort mortality study of employees in the United States carbon black industry. J.Occup. Env. Med. 48(12): 1219-1229.

Driscoll KE, Deyo LC, Carter JM, Howard BW, Hassenbein DG and Bertram TA (1997) Effects of particle exposure and particle-elicited inflammatory cells on mutation in rat alveolar epithelial cells. Carcinogenesis 18(2) 423-430.

Gardiner K, van Tongeren M, Harrington M. (2001) Respiratory health effects from exposure to carbon black: Results of the phase 2 and 3 cross sectional studies in the European carbon black manufacturing industry. Occup. Env. Med. 58: 496-503.

Harber P, Muranko H, Solis S, Torossian A, Merz B. (2003) Effect of carbon black exposure on respiratory function and symptoms. J. Occup. Env. Med. 45: 144-55.

ILSI Risk Science Institute Workshop: The Relevance of the Rat Lung Response to Particle to Particle Overload for Human Risk Assessment. Inh. Toxicol. 12:1-17 (2000).

International Agency for Research on Cancer: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans (2010), Vol. 93, February 1-14, 2006, Carbon Black, Titanium Dioxide, and Talc. Lyon, France.

Morfeld P, Büchte SF, Wellmann J, McCunney RJ, Piekarski C (2006). Lung cancer mortality and carbon black exposure: Cox regression analysis of a cohort from a German carbon black production plant. J. Occup.Env.Med.48(12):1230-1241.

Morfeld P and McCunney RJ, (2009). Carbon Black and lung cancer testing a novel exposure metric by multimodel inference. Am. J. Ind. Med. 52: 890-899.

Sorahan T, Hamilton L, van Tongeren M, Gardiner K, Harrington JM (2001). A cohort mortality study of U.K. carbon black workers, 1951-1996. Am. J. Ind. Med. 39(2):158-170.

Sorahan T, Harrington JM (2007) A "Lugged" Analysis of Lung Cancer Risks in UK Carbon Black Production Workers, 1951–2004. Am. J. Ind. Med. 50, 555–564.

The data and information presented herein corresponds to the present state of our knowledge and experience and is intended to describe our product with respect to possible occupational health and safety concerns. The user of this product has sole responsibility to determine the suitability of the product for any use and manner of use intended, and for determining the regulations applicable to such use in the relevant jurisdiction. This SDS is updated on a periodic basis in accordance with applicable health and safety standards.